



W ±2,0 (1080.0 MIN. - STANDARD SPRING CASSETTE)
W ±2,0 (870.0 MIN. - SHORT SPRING CASSETTE)

SECTION A-A
SCALE 1:1

24.0 CTS
FIXINGS TO SUIT M6 (NOT SUPPLIED)

NOTE
WHEN W IS 4000.0 AND ABOVE USE HEAVY DUTY HEM BAR OPTION.
IMPORTANT! HEAVY DUTY HEM BAR TO BE FITTED UP SIDE DOWN WHEN RELIEVING ROLLERS ARE USED.
WHEN D IS 3000.0 AND ABOVE RELIEVING ROLLER AND BRACKET TO BE USED AS SHOWN ON GDP10832 AT MID DISTANCE.

REMOVE ALL SHARP EDGES
IF IN DOUBT ASK DO NOT SCALE
GENERAL TOLERANCES TO ISO2768-m
ALL DIMNS.IN mm DRAWN TO BS308

THIRD ANGLE PROJECTION

This drawing is copyright and the exclusive property of GUTHRIE DOUGLAS LTD. and must not be copied, used or exhibited without prior written consent.

Guthrie Douglas
12 Heathcote Way, Heathcote Ind. Est;
Warwick, CV34 6TE, England.
Tel:(01926)452452 Fax:(01926)336417

ISSUE	01	02	03	04	05	06	07				
MOD NO.	0293	0435	0544	0631	DT13	DM24					
DATE	24.11.94	27.09.96	04:06:98	25.6.99	7.4.00	7.12.00					
APP'D	THC	THC	THC	THC	JPP	JPP					
DATE	11.07.94	24.11.94	27.09.96	04.06.98	7.4.00	7.12.00					

MATL:	REVISION	ASSEMBLY:	TITLE:
-	A	-	INSTALLATION OF TESS 400
PROTECTIVE TR'T:	SCALE:	-	STD. EXTERNAL GUIDED
-	1:2	-	SYSTEM
-	USED ON:	WEIGHT:	
-	SOLAR	-	

FILE NAME: SOLAR/GDP10831
DATE CREATED: 24.03.98
ORIG. A1 SHEET SCALE: 1:1

Drawn	Date	Checked	Date
JR	24.03.98	T.H.C	02:04:98
DRG.NO:	GDP10831/01/07		
SHEET 1 OF 1 SHEETS			